



# Carboform / EN / ISO Oil



# discharge hose

veloped for ships. The hose is flame  
extinguishing. It's persistent against  
0% aroma content. The hose is suitable for

BOPOMP® MARINE FUEL HOSE ISO  
7840:2013 A1 E10/D10 COMPATIBLE - CE - SAE J 1527:2011 USCG A1 -  
RINA - LLOYD'S REGISTER - YEAR - DN

**Heat resistance:** -20°C/+80°C

**Interior:** NBR, black, smooth

**Exterior:** CR, black, smooth, flame retardant

**Permeability:** <4g/m² per hour

**Standard:** EN/ISO 7840

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

| Inside Ø (mm) | Outside Ø (mm) | Weight(kg/m) | Operating pressure/Bursting pressure | Article number |
|---------------|----------------|--------------|--------------------------------------|----------------|
| 6             | 15             | 0,24         | 8bar / 14 bar                        | 3305 006000    |
| 8             | 16             | 0,25         | 8bar / 14 bar                        | 3305 008000    |
| 10            | 18             | 0,28         | 8bar / 14 bar                        | 3305 010000    |
| 12            | 21             | 0,36         | 3,5 bar / 10 bar                     | 3305 012000    |
| 16            | 26             | 0,45         | 3,5 bar / 10 bar                     | 3305 016000    |
| 19            | 29             | 0,5          | 3,5 bar / 10 bar                     | 3305 019000    |