



CP HiTex 467 Welding (
sparks or welding sparks



p hose) for flying

gases and for dust, powder, fibres

PROPERTIES

- very good resistance to flying sparks and welding sparks
- fabric reinforced
- abrasion protection via external clamp profile
- secure clamping of the wall within the clamp profile
- highly flexible + compressible 4:1
- extremely heat resistant
- flame-retardant
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

TEMPERATURE RANGE

- -70°C to 260°C
- short time to 280°C

DELIVERY VARIANTS

- further diameters and lengths available on request
- black (standard)
- stainless steel (INOX) clamp profile
- double-layer

DESIGN

- CP construction
- 1. clamp profile supporting spiral: galvanised steel
- 2. fabric-reinforced tape; wall: special-coated high-temperature fabric


Temperatur resistance: -70°C / +260°C (rövid ideig +280°C)

Construction: nagy hőállóságú többrétegű szövet

Inside: Fekete

outside: Fekete, külső hoganyzott acél spirállal

Manufacturing length: 3 és 6 m – más hosszokban is gyártható



Will be manufactured with short delivery time

Inner diameter (mm)	Outer diameter (mm)			Bending radius (mm)	Article Nr.
80	92			24	467-0080-0000
100-102	112			28	467-0100-0000
120	132			32	467-0120-0000
150-152	162			38	467-0150-0000
200-203	212	0,15	0,02	48	467-0200-0000
250	262	0,1	0,012	58	467-0250-0000
350	362	0,055	0,006	78	467-0350-0000

